



PPK FABRICANDO DE S.A.DE C.V.



6204LU Bearing 2D drawings and 3D CAD models

Japan bearing NTN 6204LU 6204LLU
WARRANTY 2 YEARS

Bearing No. 6204LU

Size	20x47x14 mm
Bore Diameter	20,000 mm
Outer Diameter	47,000 mm
Width	14,000 mm
d	20,000 mm
D	47,000 mm
B	14,000 mm
C	14,000 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.11 kg
Dynamic load, C	12.8 kN
Static load, C0	6.65 kN
Fatigue limit load, Cu	0.3 kN
f0	13.2
Nlim (grease)	10,000 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.12 Hz
Characteristic outer ring frequency, BPF0	3.08 Hz
Characteristic inner ring	4.92 Hz



PPK FABRICANDO DE S.A. DE C.V.

frequency, BPFI	
da min	25 mm
da max	28 mm
Da max	42 mm
ra max	1 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.099
EAN	4547359353570
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



PPK FABRICANDO DE S.A. DE C.V.

Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6204LU/3AS
Outer Race Width	0.551 Inch 14 Millimeter
Bore	0.787 Inch 20 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
bore diameter:	20 mm
internal clearance:	CN
outside diameter:	47 mm
operating temperature range:	-40 to 250 ° F ° F
overall width:	14 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
manufacturer upc number:	4547359353570